



TOP SIDE LOADER

Washer/Extractor



U.S.A.

ISO 9001 Certified

All Braun Products are Proudly
Manufactured in the U.S.A.

gabraun.com

TOP SIDE LOADER



TOUCH SCREEN CONTROLS

Standard on all Braun TSL machines, touch screen controls are simple, intuitive, and easy to use.



Operators can pre-program and time every cycle and water temperature and level to an exacting degree.

COMPETITIVE ADVANTAGES

Installation Flexibility

The Braun TSL is easy to install with five possible drain valve locations and trench level monitoring allowing for use in marginal drain situations.

Single Shell Door

Unlike other manufacturer's machines that have several doors, the single door on the Braun TSL ergonomically reduces the operator's repetitive motions resulting in a significant reduction of potential repetitive motion injuries.

Others

- Large cylinder
- Smaller footprint
- More efficient load and unload times
- Lower operational costs
- Proven durability


STANDARD MODELS

The Braun Top Side Loader (TSL) is available in split two-pocket and three-pocket models, and capacities of 200, 400, 600 and 800 pounds. Single motor drive is currently standard on all 200, 400 and 600 lb. machines.

Gravity assist makes loading and unloading easy and convenient. During loading the TSL rotates the cylinder door opening directly to the line of gravity. Items fall into the cylinder easily, allowing gravity to do the work. This also makes the Braun TSL ideal for overhead rail systems. The cylinder door can also position down to just 37 inches for easy hand loading. At the end of the wash cycle the TSL provides an obstruction-free, fast, gravity-assisted unload.

BRAUN'S NEUTRON SUSPENSION

- Unsurpassed vibration dampening allows for installation without a foundation, even on upper floors that can hold the static weight of the machine!
- Isolates vibration from the workspace
- Optical balance monitoring system
- Promotes less wear on major end components for exceptional durability and machine longevity
- Provides for consistent wash performance
- No air bags to maintain



Top Side Loader
Available with split
two-pocket and
three-pocket models.



The cylinder's smooth finish helps to minimize degradation of the items processed and significantly reduces the production of lint.



MEDICARE MODELS

Available in split two-pocket and three-pocket models, and capacities of 200, 400, 600 and 800 pounds. Single motor drive is currently standard on all 200, 400, and 600 lb. machines.

Medicare TSL Washer/Extractors offer the same competitive advantages and function with the same key features as our standard models, including gravity assist loading and unloading, Neutron suspension and touch screen controls.

Medicare Models
The Medicare models are designed for laundries requiring a contamination-free, clean room environment.

CROSS CONTAMINATION PREVENTION

The Medicare models are designed for laundries requiring a contamination-free, clean room environment. Soiled laundry loads from one side; clean laundry unloads from the other. A full wall barrier and patented Mediflow negative air-flow system prevent cross-contamination of goods during the process.



TSL MODEL

Specifications

TSL Model	Max. Recommended Capacity – lbs./Kg	Cylinder Dia. x Depth – inches/mm	Cylinder Volume – Cubic Ft./Cubic Meters	Cylinder Door Area Open for Loading – Sq. Inches/Sq. cm	Extract or Single Motor Drive - H.P.*	Extract Speed – R.P.M.	Wash Motor – H.P.	Wash Speed R.P.M.	Hgt. of Unloading Doors Above Floor – Inches/mm	Automatic Drain Valves – Inches/mm	Automatic Inlet Valves – Inches/mm	Steam Valve – Inches/mm	Overall Width – Inches/mm	Overall Depth – Inches/mm	Overall Height – Inches/mm	Approx. Domestic Shipping Wt. (Net) – Lbs./Kg	Approx. Export Shipping Wt. – Lbs./Kg	Export Cubage Cubic Ft./Cubic Meters
200 Neutron	230 105	46x45 1168x1143	43.3 1.125	600 3871	20	*		*	37 940	6 152	2 51	3/4 19	84 2135	75 1905	91 2310	9300 4218	10,800 4898	431 12.3
200 Neutron Medicare	230 105	46x45 1168x1143	43.3 1.125	600 3871	20	*		*	37 940	6 152	2 51	3/4 19	84 2135	68 1730	91 2310	9900 4490	11,300 5125	431 12.3
400 Neutron	450 204	60x45 1524x1143	73.6 2.085	600 3871	40	*		*	37 940	8 203	2 51	1 1/4 32	95 2415	93 2360	105 2670	12,700 5760	14,600 6621	644 18.25
400 Neutron Medicare	450 204	60x45 1524x1143	73.6 2.085	600 3871	40	*		*	37 940	8 203	2 51	1 1/4 32	95 2415	88 2235	105 2670	13,800 6259	15,200 6893	644 18.25
600 Neutron	700 317	60x66 1524x1676	107.9 3.057	600 3871	40	*		*	37 940	8 203	3 76	1 1/4 32	111 2820	95 2415	107 2720	15,800 7165	18,300 8299	786 22.26
600 Neutron Medicare	700 317	60x66 1524x1676	107.9 3.057	600 3871	40	*		*	37 940	8 203	3 76	1 1/4 32	111 2820	88 2235	107 2720	16,400 7438	18,900 8571	786 22.26
800 Neutron	900 408	60x91 1524x2311	148.8 4.215	1200 7742	30	554	15	26.5	37 940	(2)8 (2)203	3 76	1 1/4 32	141 3580	95 2415	107 2720	21,350 9683	23,120 10485	937 26.54
800 Neutron Medicare	900 408	60x91 1524x2311	148.8 4.215	1200 7742	30	554	15	26.5	37 940	(2)8 (2)203	3 76	1 1/4 32	141 3580	88 2235	107 2720	22,850 10,363	23,870 10825	937 26.54

Standard Electrical Specifications: 480 volts, 3 phase, 60 cycle A.C.

Note: All other voltages will require a transformer to either step up or step down voltage to 480/3/60.
For 380/3/50 or 380/3/60, please consult your Braun sales representative.

* user programmable



ISO 9001 CERTIFIED

G.A. Braun, Inc.
79 General Irwin Boulevard
N. Syracuse, NY 13212

Mail to:
P.O. Box 3029
Syracuse, NY 13220-3029

Phone
1-800-432-7286

Fax
(315) 475-4130

Parts Help Desk
1-800-432-7286 X 1

Service Help Desk
1-800-432-7286 X 2



U.S.A.

All Braun Products are Proudly
Manufactured in the U.S.A.